

Application No. 10/750541  
Page 2

FEB 02 2007  
Amendment  
Attorney Docket No. S63.2B-13170-US01

**Amendments To The Claims:**

1. (Currently Amended) A microsurgical balloon which comprises: an elongated, inflatable balloon having an outer surface and defining a longitudinal axis, wherein said surface of said balloon is distanced radially from said axis when said balloon is in an inflated configuration and said surface is collapsed along said axis when said balloon is in a deflated configuration; at least one incising component positioned on said surface of said balloon for movement therewith; a pad having an outer surface, wherein said pad is positioned on said balloon, spaced apart from, substantially parallel to and juxtaposed with said incising component, in the deflated configuration said outer surface of said pad being engaged to the incising component, in the inflated configuration said incising component being removed from engagement with said pad such that said pad does not contact said incising component said pad being located to engage said incising component with said outer surface of said pad to prevent damage to said balloon by said incising component when said balloon is in a deflated configuration.
2. (Original) A balloon as recited in claim 1 wherein said pad comprises a plurality of axially aligned sections.
3. (Original) A balloon as recited in claim 1 wherein said pad is formed on said outer surface of said balloon as a homogeneous structure with said balloon.
4. (Original) A balloon as recited in claim 1 wherein said incising component comprises a base and an elongated blade, and further wherein said base is mounted on said outer surface of said balloon, and said elongated blade is mounted on said base.
5. (Original) A balloon as recited in claim 4 wherein said pad is located to engage said

*Application No. 10/750541*  
*Page 3*

*Amendment*  
*Attorney Docket No. S63.2B-13170-US01*

base when said balloon is in its deflated configuration.

6. (Original) A balloon as recited in claim 1 wherein a pad is positioned on either side of said incising component.

7. (Original) A balloon as recited in claim 1 wherein said balloon includes a plurality of incising components mounted on said balloon, axially oriented and substantially parallel to said axis of said balloon.

8. (Original) A balloon as recited in claim 1 wherein said balloon includes a plurality of incising components mounted azimuthally on said balloon.

9. (Original) A balloon as recited in claim 4 wherein said base is formed with a plurality of stiffeners.

10. (Previously Presented) A system for protecting a balloon in the vasculature of a patient during a vessel dilation procedure, said system comprising: an elongated, inflatable balloon having an outer surface and defining a longitudinal axis, wherein said surface of said balloon is distanced radially from said axis when said balloon is in an inflated configuration and said surface is collapsed along said axis when said balloon is in a deflated configuration; an inflation means for moving the balloon between its deflated configuration and its inflated configuration; an incising means positioned on said outer surface of said balloon for movement therewith for incising the vessel when said balloon is in its inflated configuration; a protective means positioned on said outer surface of said balloon, spaced apart from, substantially parallel to and juxtaposed with said incising means, in the deflated configuration said protective means being engaged to the incising means, in the inflated configuration said incising means being removed from engagement with said protective means such that protective means is not in contact with said incising

*Application No. 10/750541*  
*Page 4*

*Amendment*  
*Attorney Docket No. S63.2B-13170-US01*

~~means said protective means being located to engage with said incising means to prevent damage to said balloon by said incising means when said balloon is in its deflated configuration.~~

11. (Original) A system as recited in claim 10 wherein said protective means comprises a pad, and further wherein said pad comprises a plurality of axially aligned sections.

12. (Original) A system as recited in claim 10 wherein said protective means and said balloon are a homogeneous structure.

13. (Original) A system as recited in claim 10 wherein said incising means comprises a base and an elongated blade, and further wherein said base is mounted on said outer surface of said balloon, and said elongated blade is mounted on said base.

14. (Original) A system as recited in claim 13 wherein said protective means is located to engage said base when said balloon is in its deflated configuration.

15. (Original) A system as recited in claim 10 wherein a pad is positioned on either side of said incising component.

16. (Original) A system as recited in claim 10 wherein said incising means comprises a plurality of elongated blades mounted on said balloon, axially oriented and substantially parallel to said axis of said balloon.

17. (Original) A system as recited in claim 13 wherein said base is formed with a plurality of stiffeners.

18. (Previously Presented) A method for protecting a balloon in the vasculature of a patient during a vessel dilation procedure which comprises the steps of: providing an elongated, inflatable balloon having an outer surface and defining a longitudinal axis, wherein said surface of said balloon is distanced radially from said axis when said

Application No. 10/750541  
Page 5

Amendment  
Attorney Docket No. S63.2B-13170-US01

balloon is in an inflated configuration, and said surface is collapsed along said axis when said balloon is in a deflated configuration, with at least one incising component positioned on said surface of said balloon, and at least one pad having an outer surface, wherein said pad is positioned on said balloon, spaced apart from, substantially parallel to and juxtaposed with said incising component, and further wherein in the deflated configuration said outer surface of said pad is engaged to the incising component, in the inflated configuration said incising component is removed from engagement with said pad such that said pad does not contact said incising component ~~said pad is located to engage said incising component with said outer surface of said pad to prevent damage to said balloon by said incising component when said balloon is in its deflated configuration;~~ inserting said balloon in its deflated configuration into the vasculature of a patient; inflating said balloon into its inflated configuration for emplacement of said incising component in said vasculature of said patient; and deflating said balloon to return said balloon substantially to its deflated configuration for removal of said incising component from said vasculature of said patient.

19. (Original) A method as recited in claim 18 wherein said pad and said balloon are a homogeneous structure.

20. (Original) A method as recited in claim 18 wherein a pad is positioned on either side of said incising component.

21. (Original) A method as recited in claim 18 wherein said incising component comprises a base and an elongated blade, and wherein said base is mounted on said outer surface of said balloon, and said elongated blade is mounted on said base.